



- A) Lift Height: 112" - 9'4"
- B) Clearance: 97" - 8'1"
- C) Bucket Roll Back Angle: 20°  
Bucket Dump Angle: 42°
- D) Reach at Max Height: 28"
- E) Reach at Ground Level: 18"

	2500 PSI	3000 PSI
Lift Capacity - AWC* <small>(31.5" forward from pin)</small>	3000	3600
Lift Capacity - Pivot Pin	4395	5275

\*AWC - Actual Working Capacity

## PACKAGE COMPONENTS

- Hydraulic Power-Mount™
- Quick-Attach
- Hose Kit
- Standard Bracket Set
- MA-40 Hydraulic Manifold
- Bucket Gauge Rod
- 2-1/2" Lift Cylinders
- 2" Bucket Cylinders
- 60" Bucket
- 72" Bucket (opt)
- 66" & 72" Skid-Steer Bucket & Adapter (opt)

## LOADER SPECIFIC UPGRADES & ATTACHMENTS

### Loader Upgrades

- 3rd Steel Line
- Rotational Indicators
- Under Pressure Manifold
- Hydra-Snap™
- Level UP Advantage
- Comfort Ride

### Speciality Buckets

- Tine Bucket

### Attachments - Hay Handling

- 2-Prong Bale Spear
- 3-Prong Bale Spear
- Stack Saver I & II

### Attachments - Material Handling

- Brush Crusher™
- Brush Crusher™ Finishing Teeth
- Bucket Teeth for 60" & 72" Bucket
- Rake Teeth
- 42" Fork Lift
- 48" Fork Lift
- Extendable Boom

### Additional Attachments

- 72" V-Plow
- Dual Changer Max for Bucket
- Quick Attach Adapters



**WESTENDORF MANUFACTURING CO. INC.**

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712) 423-2762 • FAX: (712) 423-1460  
Email: sales@westendorfmfg.com Website: www.loaders.com