



- A) Lift Height: 144" - 12'
- B) Clearance: 120" - 10'
- C) Bucket Roll Back Angle: 12"
- D) Reach at Max Height: 32"
- E) Reach at Ground Level: 28"

|   | 2500 PSI | 3000 PSI |
|---|----------|----------|
| Lift Capacity - AWC*<br><small>(31.5" forward from pin)</small> | 3100     | 3720     |
| Lift Capacity - Pivot Pin                                       | 4540     | 5450     |

\*AWC - Actual Working Capacity

## PACKAGE COMPONENTS

- Hydraulic Power-Mount™
- Snap-Attach™
- Hose Kit
- Standard Bracket Set
- MA-40 Hydraulic Manifold
- Bucket Gauge Rod
- 2-1/2" Lift Cylinders
- 2-1/2" Bucket Cylinders
- 72" Bucket
- 84" Bucket (opt)

## LOADER SPECIFIC UPGRADES & ATTACHMENTS

### Loader Upgrades

- 3rd Steel Line
- Back Drag Blade
- Rotational Indicators
- Under Pressure Manifold
- Hydra-Snap™
- Level UP Advantage
- Comfort Ride

### Speciality Buckets

- Fork Bucket
- Tine Bucket

### Attachments - Hay Handling

- Bucket Bale Spear
- 2-Prong Bale Spear
- 3-Prong Bale Spear
- 4-Prong Bale Spear
- Stack Saver I & II
- Bale Handler
- Bale Grab
- Squeezer™

### Attachments - Material Handling

- Brush Crusher™
- Brush Crusher™ Finishing Teeth
- Bucket Teeth for 72" Bucket
- Rake Teeth

- Sabretooth
- Monster Grab Fork
- 42" Fork Lift
- 48" Fork Lift
- Extendable Boom

### Additional Attachments

- 84" Dozer Blade
- 96" V-Plow
- 96" Snow Scraper
- Dual Changer Max for bucket
- Snap-Attach™ Adapters - Set (2)
- Snap-Attach™ Synchronizer



**WESTENDORF MANUFACTURING CO. INC.**

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712) 423-2762 • FAX: (712) 423-1460  
Email: sales@westendorfmfg.com Website: www.loaders.com