



- A) Lift Height: 125" - 10'5"
- B) Clearance: 100" - 8'4"
- C) Bucket Roll Back Angle: 27°
Bucket Dump Angle: 45°
- D) Reach at Max Height: 31"
- E) Reach at Ground Level: 19.5"

	2500 PSI	3000 PSI
Lift Capacity - AWC* <small>(31.5" forward from pin)</small>	3000	3600
Lift Capacity - Pivot Pin	4395	5275

*AWC - Actual Working Capacity

PACKAGE COMPONENTS

- Hydraulic Power-Mount™
- Snap-Attach™
- Hose Kit
- Standard Bracket Set
- MA-40 Hydraulic Manifold
- Bucket Gauge Rod
- 3" Lift Cylinders
- 2-1/2" Bucket Cylinders
- 72" Bucket
- 84" Bucket (opt)
- 72" Skid Steer Bucket & Adapter (opt)

LOADER SPECIFIC UPGRADES & ATTACHMENTS

Loader Upgrades

- Add-on Mechanical Self-Leveling
- 3rd Steel Line
- Back Drag Blade
- Rotational Indicators
- Under Pressure Manifold
- Hydra-Snap™
- Level UP Advantage
- Comfort Ride

Speciality Buckets

- High Volume Low Density
- Fork Bucket
- Tine Bucket

Attachments - Material Handling

- Brush Crusher™
- Brush Crusher™ Finishing Teeth
- Bucket Teeth
- Rake Teeth
- Sabretooth
- Jiffy Monster Grab Fork
- 42" Fork Lift
- 48" Fork Lift
- Extendable Boom

Attachments - Hay Handling

- Bucket Bale Spear
- 2-Prong Bale Spear
- 3-Prong Bale Spear

4-Prong Bale Spear

- Stack Saver I & II
- Bale Handler
- Bale Grab
- Squeezer™

Additional Attachments

- 84" Dozer Blade
- 96" V-Plow
- 96" Snow Scraper
- Dual Changer Max for bucket
- Snap-Attach™ Adapters - Set (2)
- Snap-Attach™ Synchronizer
- 2'6" Height Extension



WESTENDORF MANUFACTURING CO. INC.

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712) 423-2762 • FAX: (712) 423-1460
Email: sales@westendorfmfg.com Website: www.loaders.com