



- A) Lift Height: **170" - 14'5"**
- B) Clearance: **128" - 10'8"**
- C) Bucket Roll Back Angle: **36°**  
Bucket Dump Angle: **Near 90°**
- D) Reach at Max Height: **14"**
- E) Reach at Ground Level: **27"**

	2500 PSI	3000 PSI
<b>Lift Capacity - AWC*</b> <small>(31.5" forward from pin)</small>	3900	4680
<b>Lift Capacity - Pivot Pin</b>	5710	6850

\*AWC - Actual Working Capacity

## PACKAGE COMPONENTS

- Hydraulic Power-Mount™
- Snap-Attach™
- Hose Kit
- Standard Bracket Set
- MA-280 Hydra-Snap™ Hydraulic Manifold
- Bucket Level Indicator & Height Indicator
- 3" Lift Cylinders
- 3-1/2" Bucket Cylinders
- 84" HD Contoured Bucket
- 96" HD Contoured Bucket (opt)

## LOADER SPECIFIC UPGRADES & ATTACHMENTS

### Loader Upgrades

- 3rd Steel Line w/ MTD Couplers
- Back Drag Blade
- Level UP Advantage
- Comfort Ride

### Speciality Buckets

- Feed Bunk Bucket
- Z-47 Feeder Bucket
- Fork Bucket
- Tine Bucket

### Attachments - Material Handling

- Brush Crusher™
- Brush Crusher™ Finishing Teeth
- 72" Bucket Teeth
- 84" Bucket Teeth 84" & 96" Buckets
- Sabretooth
- Cat Claw 3-D Grab Fork
- 42" Fork Lift
- 48" Fork Lift
- Extendable Boom

### Attachments - Hay Handling

- 2-Prong Bale Spear
- 3-Prong Bale Spear
- 4-Prong Bale Spear
- Stack Saver I & II
- Bale Handler
- Bale Grab
- Squeezer™

### Additional Attachments

- 84" Dozer Blade
- 96" V-Plow
- 96" Snow Scraper
- Dual Changer Max for bucket
- Snap-Attach™ Adapters - Set (2)
- Snap-Attach™ Synchronizer



**WESTENDORF MANUFACTURING CO. INC.**

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712) 423-2762 • FAX: (712) 423-1460  
Email: sales@westendorfmfg.com Website: www.loaders.com