



- A) Lift Height: **86" - 7'2"**
- B) Clearance: **69" - 5'9"**
- C) Bucket Roll Back Angle: **15°**  
Bucket Dump Angle: **45°**
- D) Reach at Max Height: **22"**
- E) Reach at Ground Level: **12"**

	1800 PSI	2200 PSI
Lift Capacity - AWC* (31.5" forward from pin)	700	855
Lift Capacity - Pivot Pin	940	1150

\*AWC - Actual Working Capacity

## PACKAGE COMPONENTS

- Hydraulic Power-Mount™
- Hose Kit
- Standard Bracket Set
- One Lever Joystick with Valve and Manifold Kit
- Bucket Gauge Rod
- 1-1/2" Lift Cylinders
- 1-3/4" Bucket Cylinders
- 48" Bucket
- 54" Bucket (opt)

## LOADER SPECIFIC UPGRADES & ATTACHMENTS

### Loader Upgrades

- Hydra-Snap™
- Hydraulic Valve Block
- Comfort Ride
- Joystick w/ Power Beyond
- 48" Bucket Teeth
- 60" Dozer Blade
- Ballast 3 Pt. Barrel Holder
- Forklift with 42" Teeth
- Brush Crusher™



**WESTENDORF MANUFACTURING CO. INC.**

P.O. BOX 29 • ONAWA, IA 51040 • PH: (712)423-2762 • FAX:(712)423-1460  
Email: sales@westendorfmfg.com Website: www.loaders.com